


WOOD SUPPORTS NUMBER & SIZE FOR STANDARD BLANK		
SHAPE	SIZE	POSTS
	24"	ONE (1)- 4" × 4"
	30 "	ONE (1)- 4" x 4"
	36 "	ONE (1)- 4" x 6"
	48 "	TWO (2)- 4" × 6"
	30 "	ONE (1)- 4" x 4"
	36 "	ONE (1)- 4" x 4"
	48 "	TWO (2)- 4" x 4"
	60 "	TWO (2)- 4" x 4"
	12" x 18"	ONE (1)- 4" x 4"
	18" × 24"	ONE (1)- 4" x 4"
	24" x 30"	ONE (1)- 4" x 4"
	30" x 36"	ONE (1)- 4" x 6"
	36" x 48"	TWO (2)- 4" x 4"
	48" × 60"	TWO (2)- 4" x 6"
	21" x 15"	ONE (1)- 4" x 4"
	24" × 12"	ONE (1)- 4" x 4"
	24" × 18"	ONE (1)- 4" x 4"
	30" × 15"	ONE (1)- 4" x 4"
	30" x 24"	ONE (1)- 4" x 4"
	36" x 12"	ONE (1)- 4" x 4"
	36" x 24"	TWO (2)- 4" x 4"
	48" x 24"	TWO (2)- 4" x 4"
	48" x 36"	TWO (2)- 4" x 4"
	60" × 24"	TWO (2)- 4" x 4"
	60" × 36"	TWO (2)- 4" x 4"
	18"	ONE (1)- 4" x 4"
	24"	ONE (1)- 4" x 4"
	30 "	ONE (1)- 4" x 4"
	36 "	TWO (2)- 4" x 4"
	48"	TWO (2)- 4" x 6"
	24"	ONE (1)- 4" x 4"
	30"	ONE (1)- 4" x 4"
	36 "	ONE (1)- 4" × 6"
	48"	TWO (2)- 4" x 6"
	60"	TWO (2)- 4" x 6";
	24" × 24"	ONE (1)- 4" x 4"
ROUTE	30" × 24"	ONE (1)- 4" x 4"
MARKER ASSEMBLY	36" × 36"	DNE (1)- 4" x 6"
AJJEMBEI	45" × 36"	TWO (2)- 4" x 4"
* *	72" × 48"	TWO (2)- 4' × 6"
	• 84" × 72"	TWO (2)-6" x 6"
MOLE SPACINGS VARY FROM FEDERAL BLANK STANDARDS		
** (SEE MD 812.03)		
SIGN BEHIND TRAFFIC BARRIER		







NOTES:

- 1. SPACING MAY BE VARIED TO MEET FHWA BREAKAWAY REOUIREMENTS. (NO MORE THAN TWO (2) 4" x 4" OR TWO DRILLED 4" x 6" POSTS WITHIN A 7'-O" DISTANCE). (A MINIMUM 7'-O" SPACING BETWEEN ALL 6" x 6" OR 6" x 8" POSTS).
- 2. REFER TO APPROPRIATE 800 SERIES STANDARD PLATE FOR BREAKAWAY WOOD POST MODIFICATIONS.

GUIDE SIGN SUPPORT SPACING

SPECIFICATION 812, 813

APPROVED

DIRECTOR - OFFICE OF TRAFFIC AND SAFETY

APPROVAL • SHA
REVISIONS HIGHWAY ADMINISTRATION

APPROVAL 2-21-95 APPROVAL 2-21-95

10-1-01

REVISED

StateHighway

2-1-01

Maryland Department of Transportation STATE HIGHWAY ADMINISTRATION

STANDARDS FOR HIGHWAYS AND INCIDENTAL STRUCTURES

WOOD SIGN SUPPORTS POSTS SIZES & SPACING

STANDARD NO.

MD 812.04